

100-200kW

A clean and simple design
based on a box-type design

	100kW	200kW
Input Source	3Ø, AC380V ±10%	
Max. Input Capacity	110kVA	110kVA
Output Power	100kW (DC 1ch or 2ch)	200kW (DC 1ch or 2ch)
Max Current	Max. 200A	
Plug Type	CCS 1 (2ch)	
Compliance	KC, OCPP 1.6	
Frequency	60Hz	
Output Voltage Range	DC 150 ~ 1000V	
Power factor	> 0.95	
THD	< 5% @Full Power	
Voltage & Current Accuracy	1.0% @Full Scale	
Efficiency	> 94%	
Communication	DIN70121, LAN	
Charge cable	6M	
Payment System	RFID, Membership, Credit Card	
Display	12.1" Touch LCD Display	
Operating Temperature	-20 ~ 40°C	
Operating Humidity	5% ~ 95%	
IP Grade	IP44	
Protection	Under Voltage Protection, Over Voltage Protection, Over Current Protection, Over Temperature Protection	
Status Indication	Status LED	
Dimension (WxDxH, mm)	536 x 853 x 1600	536 x 853 x 1800
Dimension (WxDxH, ft)	1.76 x 2.80 x 5.25	1.76 x 2.80 x 5.91

Subject to technical change without notice. The information in this brochure contains only general descriptions or performance characteristics which may vary in actual cases.

