

240kW

A clean and simple design
based on a box-type design

	Dispenser	Powerbank
Communication	ISO/IEC15118, DIN70121, LAN	
LED Indicator	LED 1 Indicator	
Operating Temperature	-20 ~ 40°C	
IP Grade	IP44	
Payment System	RFID, Membership, Credit Card	
Display	12.1" Touch LCD Display	
Operating Humidity	5% ~ 95%	
Compliance	OCCP 1.6	
Dimension (WxDxH, mm)	500 x 300 x 1600	700 x 800 x 2000
Dimension (WxDxH, ft)	1.64 x 0.98 x 5.24	2.29 x 2.62 x 6.56
Protection	Under Voltage Protection, Over Voltage Protection, Over Current Protection, Over Temperature Protection	
Input Source	3Ø, AC380V ±10%	
Max. Input Capacity	330kVA / 264kVA	
Frequency	60Hz	
Output Power	150kW * 2ch / 120kW * 2ch	
Max Current	DC 150 ~ 1000V	
Power Factor	> 0.95	
THD	< 5% @Full Power	
Voltage & Current Accuracy	1.0% @Full Scale	
Efficiency	> 94%	
Plug Type	CCS 1, CCS 2	
Charge Cable	6M	

Subject to technical change without notice. The information in this brochure contains only general descriptions or performance characteristics which may vary in actual cases.

