

400kW

A clean and simple design based on a box-type design

	Dispenser (1ch)	Dispenser (2ch)
Input Source	US : 3Ø, AC480V ±10% / EU : 3Ø, AC400V ±10%	
Max. Input Capacity	430kVA	
Output Power	DP : 400kW*1ch / PB : 400kW	DP : 200kW*2ch / PB : 400kW
Output Voltage Range	DC 150 ~ 920Vdc	
Output Current	400A	ch@200A
Voltage & Current Accuracy	1.0% @Full Scale	
Efficiency	> 94%	
Communication	ISO / IEC15118, DIN70121, LAN	
Plug Type	CCS1 / CCS2 (Water Cooled Cable) / NACS	CCS1 / CCS2 / NACS
Payment	RFID Card, Credit Card	
Display	12.1" LCD Screen	
Operating Temperature	-20 ~ 50°C (Option : -35 ~ 50°C)	
IP Grade	IP54	
Protection	Under Voltage Protection, Over Voltage Protection, Over Current Protection, Over Temperature Protection, etc.	
Dimension (WxDxH, mm)	DP : 600 x 390 x 2350 PB : 700 x 800 x 2000 (TBD)	DP : 600 x 290 x 2350 PB : 700 x 800 x 2000 (TBD)
Dimension (WxDxH, ft)	DP : 1.96 x 1.27 x 7.70 PB : 2.29 x 2.62 x 6.56 (TBD)	DP : 1.96 x 0.95 x 7.70 PB : 2.29 x 2.62 x 6.56 (TBD)

Subject to technical change without notice. The information in this brochure contains only general descriptions or performance characteristics which may vary in actual cases.